

EVO52701967

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

APPLICATION FOR LETTERS PATENT

**SYSTEM AND METHOD FOR STORING EVENTS TO
ENHANCE INTRUSION DETECTION**

Inventor(s):

Bhalchandra Pandit

Maximilian Agner

ATTORNEY'S DOCKET NO. MS1-898US

100765039-031306

20070609 09:43:20

TECHNICAL FIELD

This invention relates to intrusion detection, and more particularly, to systems and methods for storing events to enhance intrusion detection in a host based intrusion detection system.

BACKGROUND

Detecting computer hackers, unauthorized computer operations or other abnormal anomalies that can compromise computer networks and/or sensitive data stored therein, is increasingly becoming more difficult. Most systems keep track of potentially security sensitive events that occur on those systems. These are called audit events. The audit events are stored in a secure log referred to as a security event log. In larger server environments, where there may be multiple networks feeding into a central server, it is not unusual to track 500 million audit events in a month or hundreds of audit events per second.

Now, when an intrusion or any type of security irregularity (e.g., a break-in), is suspected in a network, it is necessary to review the event log in an attempt to identify the root cause of the suspected irregularity. Current software intrusion products are often unable to timely search such massive amounts of data and adroitly identify the suspected irregularity. Currently it may take hours or several days to search through the logs to identify the irregularity and take corrective action. Many times queries need to be tested, updated and often a manual review of certain audit events is necessary to identify the root cause of an irregularity. Until the culprit of a security irregularity is identified a network remains vulnerable to continued penetration, potentially causing data or service to be severely compromised.

1 **SUMMARY**

2 A system and method for storing events to enhance intrusion detection is
3 described. In one exemplary implementation, an event is received. The event
4 includes a data section containing a set of strings each having an event field. A
5 definition table is referenced to determine locations of event fields in the data
6 section of the event. The event fields are stored in a database record
7 corresponding to event field locations referenced from the definition table.

8
9 **BRIEF DESCRIPTION OF THE DRAWINGS**

10 The detailed description is described with reference to the accompanying
11 figures. In the figures, the left-most digit(s) of a reference number identifies the
12 figure in which the reference number first appears.

13 Fig. 1 is a block diagram of a system for storing events to enhance intrusion
14 detection.

15 FIG. 1A illustrates a representative example of a single security sensitive
16 event formatted to make it readable by a human.

17 FIG. 2 illustrates an event schema for a particular event.

18 FIG. 3 is a process for generating a definition table.

19 FIG. 4 shows an exemplary definition table.

20 FIG. 5 is a flow chart illustrating a process for storing event fields in the
21 event database.

22 FIG. 6 shows an exemplary event database record for the particular event
23 shown in FIG. 1A.

FIG. 7 illustrates an example of a computing environment within which the computer, network, and system architectures described herein can be either fully or partially implemented.

DETAILED DESCRIPTION

The following discussion is directed to storing events for enhanced intrusion detection. The subject matter is described with specificity to meet statutory requirements. However, the description itself is not intended to limit the scope of this patent. Rather, the inventors have contemplated that the claimed subject matter might also be embodied in other ways, to include different elements or combinations of elements similar to the ones described in this document, in conjunction with other present or future technologies.

Exemplary System

Fig. 1 is a block diagram of a system 100 for storing events to enhance intrusion detection. System 100 includes a plurality of computers 102, 106 and a network 101. Although system 100 includes computers 102, 106 for illustration purposes, different numbers of devices and network topologies may be included. Additionally, some or the data structures (to be described) as well as modules shown in system 100 can be implemented within a computing device, such as computer 106, or can be distributed within a computing system having more than one computing device. See the description of "Exemplary Computing System and Environment" below for specific examples and implementations of networks, computing systems, computing devices, and components that can be used to

1 implement the described implementations, including computers 102, 106 and
2 network 101.

3 Network 101 can be any type of network, such as a local area network
4 (LAN) or a wide area network (WAN), using any type of network topology and
5 any network communication protocol. Furthermore, network 101 can represent a
6 combination of two or more networks. In this example, network 101 includes
7 logical connections to facilitate data communication between the computers 102
8 and computer 106.

9 Besides computers 102, 106, system 100 includes two data structures in the
10 form of an event database 112 and an event definition table 114. The two data
11 structures may be stored locally with computer 106 or in any other accessible
12 location such as mass storage for system 100. In the described implementation,
13 the databases are a SQL database, but other types of databases could easily be
14 employed.

15 Computers 102 operate under the control of a Microsoft® Windows®
16 brand operating system. Nevertheless, other operating systems can be used.
17 Computers 102 contain security event logs 104 which are data files that contain a
18 record of events performed by their respective computer 102. The Microsoft®
19 Windows® operating system normally maintains the record of events, which are
20 generally associated with security sensitive events relating to intrusion detection.
21 Examples of a security sensitive event includes, but is not limited to, logging-on to
22 a network, gaining access to a particular file, performing certain application level
23 tasks that are considered sensitive, gaining access to a particular object,
24 administering passwords, changing passwords, sending and/or receiving a file
25 infected with a virus, and other related events.

1 Each event is generally recorded in the event log 104. Although different
2 events might contain similar types of data, the format of the data is allowed to vary
3 significantly from one event to another. An "event" is information generated by
4 an operating system or related system when a security sensitive event is performed
5 by a client (user via a client computer). The information contains actual data that
6 identifies users or objects affected by the event. The actual data consists of two
7 sections: a header and data section.

8 The "header section" is a fixed length section of the event and has several
9 fields, including: and event type (success/failure), event source, event category,
10 event identification, date, time, user name and computer name (see FIG. 1A).

11 The "data section" is a variable length section of the event that is stored in
12 as set of strings. The number of strings present varies according to the "event
13 identification" in the Event Header Section. For example, event 0x272(==626
14 decimal) contains six strings: foo, KUMARPDOM, KUMARPDOM\foo,
15 Administrator, KUMARPDOM, (0x0, 0x237CE5) (see FIG. 1A).

16 The "event identification" (also referred to event ID) identifies the type of
17 event.

18 "Event Schema" defines how an event is formatted when it is displayed to a
19 user (see FIG. 2 for an example of an event schema for event ID 0x272).

20 "Field (or event field)" means one of the strings in the data section of an
21 event.

22 As an example, the following is a single schema that describes an "SE
23 AUDITID USER ENABLED" type of event:

24 MessageId=0x0272
25 SymbolicName=SE_AUDITID_USER_ENABLED
Language=English

User Account Enabled:%n
%tTarget Account Name:%t%1%n
%tTarget Domain:%t%2%n
%tTarget Account ID:%t%3%n
%tCaller User Name:%t%4%n
%tCaller Domain:%t%5%n
%tCaller Logon ID:%t%6%n

FIG. 1A illustrates a representative example of a single security sensitive event formatted to make it readable by a human, but stored in the event log.

The header in this example includes the following text:

MessageId=0x0272
SymbolicName=SE_AUDITID_USER_ENABLED
Language=English

In this example, the value "0x0272" is the event identification (the 0x prefix indicates the number is in hexadecimal format). Generally, the event identification follows the header text "MessageId=", regardless of the event type. Other formats could of course be used in other systems. In general, the event identification will comprises code, text or an identification number, at a consistent or identifiable location within the event, that identify the particular type of event and corresponding security sensitive event.

Following the header information, the event also includes a sequence of one or more event descriptors. In this example, each of the lines following the header is an event descriptor. Each descriptor provides different information about an event, such as the account name of a client computer, a password, target account, and so forth.

In this example, each event descriptor comprises a descriptive phrase followed by a value. For example, the first descriptor in the above example

1 contains the descriptive phrase "Target Account Name:", followed by a value.
2 The values of the multiple descriptors can be in the form of numbers, text, or other
3 information. They provide actual information about the event that corresponds to
4 the event. Generally, the initial descriptive phrase describes the nature of the
5 value that follows. For instance, if the descriptive phrase of the event descriptor is
6 "logon ID," then the value that follows the descriptive phrase corresponds to the
7 actual alphanumeric logon ID that was used in conjunction with the event
8 corresponding to the event. As another example, if the descriptive phrase of the
9 event descriptor is "target account" then the value that follows the descriptive
10 phrase indicate the actual alphanumeric target account number used in conjunction
11 with the event corresponding to the event.

12 As can be seen in the example of FIG. 1A, each event is normally stored as
13 a header followed by a concatenation of event descriptors.

14 Although the descriptive phrases are meaningful to a human user, they are
15 difficult to analyze in a computer-automated process. One significant reason for
16 this difficulty is that different types of events use different descriptive phrases to
17 describe the same types of values. Generally, the descriptive phrases are
18 generated by different teams of software designers working on different
19 application programs. Thus, although similar information might be provided in
20 different types of events, the information might be preceded by very different
21 descriptive phrases. Furthermore, the ordering of information within the events is
22 not consistent between events of different types.

23 ***Event Definition File***

24 An event definition table 114 is generated and maintained in order to allow
25 intelligent parsing of events. Generally, the event definition table contains a

record corresponding to each possible event type, and indicates the type of information found at each value location in an event of a particular event type. More specifically, the event definition table contains columns corresponding to value types that might be of particular interest when attempting to detect or trace security breaches. As an example, the Primary User (PU), the Primary Domain (PD), Primary Login (PL) Target User (TU), Target Domain (TD), etc. are all examples of some value types that might be of particular interest.

Event definition table 114 can be generated in a variety of ways. For example, it can be compiled manually, by an analyst who examines the various different types of events and notes the locations of values in the event fields within those strings. In the Windows® brand operating system environment, there are available templates that describe the data formats of different events. For example, such a template for event type 0x272 (discussed above) might appear as follows:

```

MessageId=0x0272
SymbolicName=SE_AUDITID_USER_ENABLED
Language=English
User Account Enabled:%n
%tTarget Account Name:%t%1%n
%tTarget Domain:%t%2%n
%tTarget Account ID:%t%3%n
%tCaller User Name:%t%4%n
%tCaller Domain:%t%5%n
%tCaller Logon ID:%t%6%n

```

In a template such as this, the “%t” indicates a tab character. Each descriptive phrase is followed by a “%x” placeholder, where x is a numeric integer. Each “%x” placeholder represents a location within the event at which an event field will eventually be located. A “%n” symbol indicates a new line indicator.

Based on the availability of templates such as these, it is also possible to automate the process of creating event definition table 114. Fig. 1 shows a definition module 116 that is designed to automate this process. Generally, definition module 116 works by examining the descriptive phrases of the templates and determining value types from such descriptive phrases.

Accordingly, computer 106 contains a definition-module 116 that generates an event definition table 114. The event definition table 114 provides a map for locating where particular values in the event fields are located within event descriptions of a particular event. Although computer 106 is shown to contain the definition-module 116, the module 116 can actually reside in any computer device.

Once the event definition table 114 is constructed, computer 106 can store events collected from computers 102 in the event database 112. To accomplish this, computer 106 includes an event receiver module 108 that receives the events from the computers 102. That is, the event receiver module 108 collects the various events described in FIG. 1A. The events may be collected periodically or after the occurrence of an event.

Computer 106 also includes an event-processing module 110. After the events are received, the event-processing module 110 identifies values in the event fields within an event description. The event-processing module 110 references the event definition table 114 to determine locations of the values in the event fields. Once the locations are determined, the actual values in the event fields can be stored in fields of the event database 112 that correspond to value types indicated by the event definition table 114.

1 In other words, the event definition table 114 provides a map of where
2 values in the event fields are located within events and enables the values in the
3 event fields to be stored in fields corresponding to a particular event type. This
4 permits event database 112 to be later searched during intrusion detection for a
5 particular event field by selecting the event type that corresponds to the field in the
6 event database 112 in which the event field is located. This system greatly
7 increases the efficiency of a search for a specific data (event field) during intrusion
8 detection.

9 *Generation of Event Definition File*

10 FIG. 2 illustrates an event schema for a particular event. Event schema
11 200 includes an event identification 202, event descriptions 204, and values in the
12 event fields 306. An event identification is an event identification value that
13 identifies the type of an event. The event indicator (shown as 202) is 0x272, which
14 in this example refers to event (SE_AUDITID_USER_ENABLED). Event
15 descriptions 204 are essentially the components of an event that are shown as
16 separate lines in the event schema 200. Each event description 204 in the event
17 schema provide the definition what the values in the event fields 206 pertain to.
18 For instance, the event descriptions 204 are "User Account Name," "Target
19 Account Name," "Target Domain" and so forth. The values in the event fields 206
20 provide actual information about the event descriptions, such as what values are
21 associated with of the User Account Name, Target Account Name, Target
22 Account and so forth. The event field may be numeric, alphanumeric and/or in
23 some other description format.

24 FIG. 3 is a process 300 for generating a definition table 114. FIG. 3 is a
25 process 300 for generating event definition table 114 by parsing the event schema,

1 Next, in step 306, the definition-module 116 parses each event
2 corresponding its the event indicator 202, and ascertains locations of values in the
3 event fields in the particular event that corresponds to one or more selected value
4 types. Referring to FIGS. 2 and 4, the definition-module 116 parses the first event
5 description, "Language=English" and ignores the description because it is not one
6 of the selected value types.

7 Next, in step 308, the definition-module 116 stores the location of the
8 values in the event fields 308 in the table 114. For example, for "Target Account
9 Name" the event field location is %1. So, the definition module 116 inserts an
10 event field of %1 in the TU field 402 of table 114; a %2 in the TD field, a %3 in
11 the TA field and so forth. In value type fields 402 Primary User (PU), Primary
12 Domain (PD), and Primary Logon (PL), the definition-module 116 inserts zeros as
13 defaults, because no event descriptions or values in the event fields correspond to
14 these value types in the example of event type 0x272 shown in FIG. 2. Notice that
15 the event identification 0x272 serves as a row identifier for the values in the event
16 fields associated with that event identification.

17 *Generation of Event Database 112*

18 Once the locations for the values in the event fields are stored in the event
19 definition table 114 for the events selected of interest, the event-processing
20 module 110 is able to use the definition table 114 as a reference to parse actual
21 values in the event fields located in events as the events are collected by computer
22 106. The event-processing module 110 can then store the values in the event
23 fields in the event database 112 in fields corresponding to the value types
24 indicated by the event definition table 114.

25

FIG. 5 is a flow chart illustrating a process 500 for storing values in the event fields in the event database 112. Process 500 includes steps 502 through 512. The order in which process 500 is described is not intended to be construed as a limitation. It is possible for some of the operational steps to be performed in different orders than described in process 500. In the exemplary implementation, event-receiver module 108 and event-processing module 110 implement process 500 through software. Nevertheless, process 500 can be implemented in any suitable hardware, software, firmware, or combination thereof.

In step 502, event receiver module 108 receives an event containing an event identification and event descriptions. For example, referring to FIG. 1A, the event contains event identification and event descriptions. The event-processing module 110 then identifies values in the event fields.

In step 506, once the values in the event fields are located, the event-processing module 110 locates an entry in the event definition table 114 that corresponds to the event identification of the particular event. Knowing the event identification from the received event, permits the event processing module 110 to refer to event definition table 114 by locating a matching event identification from the table 114. For example, the event identification in FIG.1A is 0x272, so the event processing module 110 is able to locate event identification in table 114 shown in FIG. 4.

Next, in step 508, the event-processing module 110 locates value types referenced from the table 114 that correspond to the values in the event fields of the received event. By referencing table 114 in FIG. 4, for instance, value type Caller Logon ID (CL) indicates that event field event identification 0x272 is %6.

1 Accordingly, the event-processing units know that the event field from the %6
2 position is a CL type of event field.

3 In step 510, the event processing module 110 creates a record in the event
4 database 112 for each received event. FIG. 6 shows, an exemplary recorded table
5 for event type indicator 0x272 from the event shown in FIG. 1A.

6 In step 512, the event processing module 110 completes the record for each
7 particular event. Event processing module 110 stores the identified values in the
8 event fields in fields of the event database 112 that correspond to the value types
9 referenced from table 114 of the values in the event fields. For example, for the
10 Caller Logon ID (CL) value type field, the event-processing module stores the
11 event field (0X0, 0X237CE5), which is the actual value for the event field for the
12 Caller Logon ID received with this event.

13 *Exemplary Computing System and Environment*

14 FIG. 7 illustrates an example of a computing environment 700 within which
15 the computer, network, and system architectures described herein can be either
16 fully or partially implemented. Exemplary computing environment 700 is only
17 one example of a computing system and is not intended to suggest any limitation
18 as to the scope of use or functionality of the network architectures. Neither should
19 the computing environment 700 be interpreted as having any dependency or
20 requirement relating to any one or combination of components illustrated in the
21 exemplary computing environment 700.

22 The computer and network architectures can be implemented with
23 numerous other general purpose or special purpose computing system
24 environments or configurations. Examples of well known computing systems,
25 environments, and/or configurations that may be suitable for use include, but are

1 not limited to, personal computers, server computers, thin clients, thick clients,
2 hand-held or laptop devices, multiprocessor systems, microprocessor-based
3 systems, set top boxes, programmable consumer electronics, network PCs,
4 minicomputers, mainframe computers, gaming consoles, distributed computing
5 environments that include any of the above systems or devices, and the like.

6 Modules 108, 110 and 116 may be described in the general context of
7 computer-executable instructions, such as program modules, being executed by a
8 computer. Generally, program modules include routines, programs, objects,
9 components, data structures, etc. that perform particular tasks or implement
10 particular abstract data types. Modules 108, 110 and 116 may also be practiced in
11 distributed computing environments where tasks are performed by remote
12 processing devices that are linked through a communications network. In a
13 distributed computing environment, program modules may be located in both local
14 and remote computer storage media including memory storage devices.

15 The computing environment 700 includes a general-purpose computing
16 system in the form of a computer 702. The components of computer 702 can
17 include, by are not limited to, one or more processors or processing units 704, a
18 system memory 706, and a system bus 708 that couples various system
19 components including the processor 704 to the system memory 706.

20 The system bus 708 represents one or more of any of several types of bus
21 structures, including a memory bus or memory controller, a peripheral bus, an
22 accelerated graphics port, and a processor or local bus using any of a variety of
23 bus architectures. By way of example, such architectures can include an Industry
24 Standard Architecture (ISA) bus, a Micro Channel Architecture (MCA) bus, an
25 Enhanced ISA (EISA) bus, a Video Electronics Standards Association (VESA)

1 local bus, and a Peripheral Component Interconnects (PCI) bus also known as a
2 Mezzanine bus.

3 Computer system 702 typically includes a variety of computer readable
4 media. Such media can be any available media that is accessible by computer 502
5 and includes both volatile and non-volatile media, removable and non-removable
6 media. The system memory 706 includes computer readable media in the form of
7 volatile memory, such as random access memory (RAM) 710, and/or non-volatile
8 memory, such as read only memory (ROM) 712. A basic input/output system
9 (BIOS) 714, containing the basic routines that help to transfer information
10 between elements within computer 702, such as during start-up, is stored in ROM
11 712. RAM 710 typically contains data and/or program modules that are
12 immediately accessible to and/or presently operated on by the processing unit 704.

13 Computer 702 can also include other removable/non-removable,
14 volatile/non-volatile computer storage media. By way of example, FIG. 7
15 illustrates a hard disk drive 716 for reading from and writing to a non-removable,
16 non-volatile magnetic media (not shown), a magnetic disk drive 718 for reading
17 from and writing to a removable, non-volatile magnetic disk 720 (e.g., a "floppy
18 disk"), and an optical disk drive 722 for reading from and/or writing to a
19 removable, non-volatile optical disk 724 such as a CD-ROM, DVD-ROM, or other
20 optical media. The hard disk drive 716, magnetic disk drive 718, and optical disk
21 drive 722 are each connected to the system bus 708 by one or more data media
22 interfaces 726. Alternatively, the hard disk drive 716, magnetic disk drive 718,
23 and optical disk drive 722 can be connected to the system bus 708 by a SCSI
24 interface (not shown).

1 limitation, communication media includes wired media such as a wired network or
2 direct-wired connection, and wireless media such as acoustic, RF, infrared, and
3 other wireless media. Combinations of any of the above are also included within
4 the scope of computer readable media.

5 A user can enter commands and information into computer system 702 via
6 input devices such as a keyboard 734 and a pointing device 736 (e.g., a "mouse").
7 Other input devices 738 (not shown specifically) may include a microphone,
8 joystick, game pad, satellite dish, serial port, scanner, and/or the like. These and
9 other input devices are connected to the processing unit 704 via input/output
10 interfaces 540 that are coupled to the system bus 708, but may be connected by
11 other interface and bus structures, such as a parallel port, game port, or a universal
12 serial bus (USB).

13 A monitor 742 or other type of display device can also be connected to the
14 system bus 708 via an interface, such as a video adapter 744. In addition to the
15 monitor 742, other output peripheral devices can include components such as
16 speakers (not shown) and a printer 746 which can be connected to computer 702
17 via the input/output interfaces 740.

18 Computer 702 can operate in a networked environment using logical
19 connections to one or more remote computers, such as a remote computing device
20 748. By way of example, the remote computing device 748 can be a personal
21 computer, portable computer, a server, a router, a network computer, a peer device
22 or other common network node, and the like. The remote computing device 748 is
23 illustrated as a portable computer that can include many or all of the elements and
24 features described herein relative to computer system 702.
25

1 Logical connections between computer 702 and the remote computer 548
2 are depicted as a local area network (LAN) 750 and a general wide area network
3 (WAN) 752. Such networking environments are commonplace in offices,
4 enterprise-wide computer networks, intranets, and the Internet. When
5 implemented in a LAN networking environment, the computer 702 is connected to
6 a local network 750 via a network interface or adapter 754. When implemented in
7 a WAN networking environment, the computer 702 typically includes a modem
8 756 or other means for establishing communications over the wide network 752.
9 The modem 756, which can be internal or external to computer 702, can be
10 connected to the system bus 708 via the input/output interfaces 740 or other
11 appropriate mechanisms. It is to be appreciated that the illustrated network
12 connections are exemplary and that other means of establishing communication
13 link(s) between the computers 702 and 748 can be employed.

14 In a networked environment, such as that illustrated with computing
15 environment 700, program modules depicted relative to the computer 702, or
16 portions thereof, may be stored in a remote memory storage device. By way of
17 example, remote application programs 758 reside on a memory device of remote
18 computer 748. For purposes of illustration, application programs and other
19 executable program components, such as the operating system, are illustrated
20 herein as discrete blocks, although it is recognized that such programs and
21 components reside at various times in different storage components of the
22 computer system 702, and are executed by the data processor(s) of the computer.

23 Conclusion

24 Although the invention has been described in language specific to structural
25 features and/or methodological acts, it is to be understood that the invention

1 defined in the appended claims is not necessarily limited to the specific features or
2 acts described. Rather, the specific features and acts are disclosed as exemplary
3 forms of implementing the claimed invention.

10076039.02102